



FLOOR | WALL

AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC
WALL & MOSAIC with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Affinity™ Cream 12 x 24 floor tile on the floor with Cream 10 x 14 wall tile and 2 x 2 mosaic on the wall.

Modern Take on a Classic Stone Look

USAGE

Floors

Walls

Countertops

F

W

C

• NATURAL ATTRIBUTES

- Subtle movement and features reminiscent of limestone contribute to its authentic natural stone look
- Warm, neutral color palette

• STYLISH DEMEANOR

- Ideal complement to contemporary designs and modern décor
- Coordinating wall, floor, mosaic and trim add finishing design touches



**POST-CONSUMER
RECYCLED MATERIALS**



**PRE-CONSUMER
RECYCLED MATERIALS**



MADE IN THE U.S.A.



REVEAL IMAGING®

All or select items within this series meet the requirements for these qualifications. For more information visit daltille.com.

**CERTIFIED
PORCELAIN™**
TILE
0.5% or less water absorption

GLAZED PORCELAIN FLOOR TILE



CREAM AF01



BEIGE AF02



GRAY AF03



BROWN AF04

GLAZED CERAMIC WALL TILE



CREAM AF01



BEIGE AF02



GRAY AF03



BROWN AF04

2 x 2 GLAZED CERAMIC MOSAIC



CREAM AF01



BEIGE AF02



GRAY AF03



BROWN AF04

AFFINITY™

GLAZED PORCELAIN FLOOR, GLAZED CERAMIC WALL & MOSAIC WITH REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	18 x 18 Floor Tile	(17-13/16" x 17-13/16") (45.20 cm x 45.20 cm)	5/16"	17.60	8
	12 x 24 Floor Tile	(11-13/16" x 23-13/16") (30.00 cm x 60.48 cm)	3/8"	15.60	8
	12 x 12 Floor Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	5/16"	14.55	15
	10 x 14* Wall Tile	(9-13/16" x 13-15/16") (24.99 cm x 35.40 cm)	5/16"	14.25	15
	2 x 2 Mosaic* (Dot-mounted on 12" x 24" Sheet)	(12" x 24" Sheet) (30.48 cm x 60.96 cm Sheet)	1/4"	24.00	12

* Glazed Ceramic

APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	✓†
Wet & Level – Interior Floor	≥ 0.42	✓†
Shower Floors (Residential or Light Commercial)	≥ 0.42	✓*
Exterior Floor Applications (including pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	✓†
Pool Linings	N/A	✓*

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:




† Wall tile not suitable for this application.

* Mosaic tile only

Floor tile suitable for exterior applications in freezing and non-freezing climates, when proper installation methods are followed.


Wall and mosaic tile suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces/ Carton
 Bullnose	P-43C9	3 x 12	30
 Wall Bullnose *	S-4310 (10" side)	3 x 10	54
 Wall Bullnose Corner *	SN-4310	3 x 3	32

* Glazed Ceramic

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>Floor: 3/16" (Overlap should not exceed 33% when installing tile with a length 15" or greater in a staggered brick-joint pattern. When multiple sizes are installed in a modular pattern, please specify same size caliber at time of order.)</p> <p>Wall: 1/16"</p> <p>Mosaic: 1/8"</p>	
	 High (V3)

PERFORMANCE CHARACTERISTICS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs	120-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.0	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Abrasion Resistance	C1027	3 (AF04) 4 (AF01-03)	N/A	3 (AF04) 4 (AF01-03)

For additional information on test results, visit us at: daltile.com/information/TestResults.

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

Not for use on ramps. Water, oil, grease, improper drainage and certain footwear can create slippery conditions. Floor applications expected to be exposed to these conditions require extra caution in product selection.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to daltile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation. For more information, visit daltile.com.



DESIGNED TO HELP EARN LEED™
CREDITS. For more detailed information,
visit daltilegreenworks.com.

7834 C. F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of
Daltile® products and information,
visit our website at daltile.com.

daltile®
IMAGINE WHAT'S POSSIBLE™

©2017 Daltile (9/17)