# MOSAIC TRADITIONS™

**GLASS & STONE MOSAICS** 



### 1 x 1 MOSAIC



Desert Dune BP94



Caramelo BP95



Oasis BP98



Zen Escape BP96



Skyline BP99



Evening Sky BP97

### 3/4 x 1-1/2 BRICK JOINT MOSAIC



Desert Dune BP94



Caramelo BP95



Oasis BP98



Zen Escape BP96



Skyline BP99



Evening Sky BP97

## 5/8 x 3 BRICK JOINT MOSAIC



Desert Dune BP94

STREET, SQUARE, SQUARE,		1 100	
DESCRIPTION OF		1	100
	_	100	-
STATE OF THE PERSON NAMED IN			_
SECURITY OF	and the last		
STREET, SQUARE, SQUARE		0000	
STREET, SQUARE, BOTTON,			
200	-	100	-12
-		_	
SECTION 2			_
SPECIAL PROPERTY.	THE REAL PROPERTY.		
0.000000		THE RESERVE	1
100			-
-	-	_	

Caramelo BP95

-	MI DESCRIPTION IN		-
	MARKET MARK	THE R. LEWIS CO., Land	-
	OR ASSESSMENT OF	-	
HOUSE		100 HOLD	
- 20000	OF RESOURCES	ALTERNATION NAMED IN	_
STATE OF	PROPERTY AND PERSONS NAMED IN	-	_
	00		
-	NAME OF TAXABLE PARTY.	<b>30</b> 10/0	_
MARKET ST	STREET, SQUARE, SQUARE	1000	
<b>BOOK</b>			_
-	OR RESIDENCE OF		
THE REAL PROPERTY.	STREET, SQUARE, SQUARE,	- FO	_
-	OUR ADDRESS OF THE	W000	
majores.	STREET, SAME	<b>100</b>	_
	MI SERVICE M	THE REAL PROPERTY.	_
-	Name and Address of the Owner, where the Owner, which is the Owner, where the Owner, which is the Owner,	1000	

Oasis BP98



Zen Escape BP96



Skyline BP99



Evening Sky BP97



## MOSAIC TRADITIONS™

**GLASS & STONE MOSAICS** 



### SIZES

		Thickness	Sq. Ft. per Carton	Pieces per Carton
	(11-7/8" x 11-7/8" sheet) (30.00 cm x 30.00 cm sheet)	4 mm	20.00	20
3/4 x 1-1/2 Brick- joint Mosaic (Mesh-mounted)	(12" x 12-5/8" sheet) (30.80 cm x 31.40 cm sheet)	4 mm	20.00	20
5/8 x 3 Brick- joint Mosaic (Mesh-mounted)	(12" x 12-7/8" sheet) (30.80 cm x 32.80 cm sheet)	4 mm	20.00	20

### **APPLICATIONS**

	Suitable
Floors	
Walls/Backsplashes	✓
Countertops	
Pool Linings	

Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

Suitable for use in wet areas such as shower walls.

### INSTALLATION

Grout Joint Recommendation	Shade Variation
1/8"	Random (V4)

### **TEST RESULTS**

	ASTM#	Abrasive and Non-Abrasive Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 100 lbs
Scratch Hardness	MOHS	4.0
Chemical Resistance	C650	Resistant

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arrangement planned prior to installation.

Since there are variations in all glass products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.2 standards.

For additional information, refer to "Factors to Consider" at daltile. com/Factors  $\,$ 







