# TILE & STONE

## **MARLOW DCO MX 8X8**

glazed porcelain





### **MARLOW DCO MX 8X8**

# TILE & STONE

Style Number	CS86Z
Construction	Porcelain
Tile Type	Floor
Tile Size	7.87" x 7.87"   20 cm x 20 cm
Edges	Pressed
Installation Area	Exteriors, Floors, Walls
Technical	
Wear Rating Group	4
Break Strength	250
Water Absorption %	0.50
DCOF	0.42

A DCOF value of > 0.42 is the new standard for tiles specified for commercial application in standard Al37.1-2012, Section 9.6. It replaces the SCOF value of > 0.60 referenced in ASTM Cl028. For more information on the correlation between the two values and about the DCOF AcuTest visit the Tile Council of North America's website: www.tcnatile.com

#### MANUFACTURER'S WARNING:

- Tiles with DCOF AcuTest values less than 0.42 are not recommended for use in areas with wet or slippery conditions. If such tiles are used as a walking surface where water, ice, oil, grease and/or other substances are present, such a condition could cause a reduction in foot traction and become unexpectedly slippery resulting in a fall and personal injury. See ANSI standard Al37.1 section 6.2.2.1.10.
- Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.
- Since there is a shade variation on all natural products, the tile and trim supplied for your particular installation may not match these samples. Final selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

#### Colors



571 Manor Mix





